

SLS40-A

Laser Scintillometer for Towers – with Beam Steering



Photo courtesy of CSIR, South Africa

The Scintec SLS40-A Scintillometer measures turbulence, heat flux and momentum flux by purely optical means. In combination with other meteorological sensors the system can determine latent heat flux or evaporation.

The SLS40-A has both built-in automatic beam steering and vibration correction. It is designed for operation on towers or other platforms which are prone to vibration or long-term-drift. Vibration effects are compensated by using the signal of four instead of two optical detectors.

Each SLS Series Scintillometer consists of a laser transmitter pointing at a receiver. Temperature fluctuations in the air cause variations of the light

intensity captured at the receiver. The scintillometer evaluates such variations to yield turbulence information.

The line averaging over the optical path results in spatially representative data and outstanding temporal resolution – a critical edge over data collected from conventional point sensors. The scintillometer provides high sensitivity and accuracy – without mechanical flow distortion or any moving part.

The proprietary displaced-beam technique of the SLS Series Scintillometers opens up access to mechanical turbulence quantities (momentum flux, kinetic-energy dissipation rate) without need to feed in any external wind data.

Features

- heat flux, momentum flux by purely optical means
- suitable for stable and unstable conditions
- measures C_n^2 , C_T^2 , l_0
- crosswind option available
- spatially averaging technique
- high temporal resolution
- low statistical noise
- no flow distortion
- easy installation and operation
- Signal Processing Unit performs all calculations
- 6 GB built-in data storage
- remote access
- beam-displacement calibration
- window heating

Applications

- turbulence studies
- air quality and atmospheric dispersion
- spatially-averaged wind measurements
- optical propagation conditions
- defence weather
- surface energy balance
- evapotranspiration monitoring
- agrometeorology, forestry
- satellite data ground truth

Scintec 

SLS40-A

Data output

Data output includes (but is not limited to):

- structure parameter of refractive index fluctuations (C_n^2)
- inner scale of refractive index fluctuations (ℓ_0)
- structure parameter of temperature fluctuations (C_T^2)
- dissipation rate of turbulent kinetic energy
- sensible heat flux
- momentum flux
- Obukhov length
- path-averaged wind speed perpendicular to the beam axis (with crosswind extension)
- mean, standard deviation, minimum and maximum of intensity
- correlation coefficient of intensity
- data quality code

| Description | Specifications | | | Remarks |
|--|--|---------------------|--------------------------|---|
| Optical wavelength | 670 nm +- 10 nm | | | visible (red) |
| Mean output power | 1 mW | | | laser safety class 2M (IIIa) |
| Beam divergence | 3.5 x 10 mrad | | | |
| Beam-steering scan cone diameter | 1 degree | | | |
| Path length | 50 - 250 m | | | others optional |
| Integration time | 1 s to 60 min | | | |
| Supply voltage and current | 12 V, 18 W | | | for transmitter, receiver, SPU |
| Data output | Ethernet, RS232 | | | 6 GB storage |
| Operating temperature | -20 to +50 °C (-5 to +120 °F) | | | |
| Dimensions | 65 x 11 x 11 cm / 60 x 11 x 11 cm 33 x 23 x 18 cm | | | transmitter / receiver SPU |
| Weights | 3.0 kg / 2.9 kg / 8.0 kg | | | transmitter / receiver / SPU |
| Measurement ranges ⁽¹⁾ | from | to | unit | Depends on |
| Structure constant C_n^2 | 1×10^{-16} | 3×10^{-12} | $m^{-2/3}$ | path length |
| Inner scale ℓ_0 | 2 | 16 | mm | path length |
| Structure constant C_T^2 | 1×10^{-4} | 3 | $K^2 m^{-2/3}$ | path length ⁽²⁾ |
| Kinetic-energy dissipation rate ϵ | 2×10^{-4} | 1 | $m^2 s^{-3}$ | path length ⁽²⁾ |
| Sensible heat flux | 2 -2 | 600 -120 | $W m^{-2}$ $W m^{-2}$ | path length and height, Obukhov length ⁽²⁾ |
| Momentum flux | -4×10^{-3} | -1.2 | $N m^2$ | path length and height, Obukhov length ⁽²⁾ |
| Wind speed | 0.01 | 10 | $m s^{-1}$ | with Crosswind Extension |

¹⁾ Typical values for path 100 m long and 2 m high; ²⁾ Values for normal temperature and pressure

Scintec AG

Willhelm-Maybach-Str. 14
72108 Rottenburg
Germany

Tel. +49 7472 98643-0
Fax +49 7472 9808714
info@scintec.com

Scintec Corporation

1730 38th Street, Boulder,
Colorado 80301
USA

Tel. +1 303 666-7000
Tel. +1 303-666-8803
ussales@scintec.com

www.scintec.com

Specifications are subject to change without notice.

